

CRACK FILLER

**READY TO USE FIBRE REINFORCED
ACRYLIC POLYMER BASED CRACK
FILLING PASTE**



TECHNICAL DATA SHEET

BENEFITS

- Ready to use.
- Excellent thixotropichness.
- Excellent adhesion.
- Easy to apply.
- Excellent finishing.
- Can be used on all common type of building interiors and exteriors.
- Dense and cohesive paste will not allow water penetration.
- High performance non structural crack filling paste.
- Allow surface to breath.
- Resistance to weather and chemical.
- Safe to use.
- Non toxic.
- Available in attractive white colour.

PRODUCT

CRACKFILL PASTE is an easy to use, acrylic polymer based crack filling paste, which ensures fibre reinforced perfect filling of cracks and will not allow water penetration.

APPLICATION

Surface Preparation: Chip out the crack in 'V' groove and clean all the debris and loose particles. Prewet the surface. The prepared surface should be free from oil, grease, dust, dirt etc.

Application: To obtain a smooth surface, use a flat tool, like a steel spatula to apply the material into the cracks.

PACKING & COVERAGE

CRACKFILL PASTE is available in 1kg, 5kg, 10kg and 20kg. plastic bucket. 1kg of CRACKFILL PASTE will approximately cover 7 to 8 running meter having the width and depth of 3mm to 4mm.

SHELF LIFE & STORAGE

CRACKFILL PASTE will have a shelf life of 12 months in unopened containers when kept in dry conditions at a temperature between 5°C to 35°C. Material must be kept under shaded area and away from direct sunlight. Storage at higher temperature or high humidity may reduce shelf life.

HEALTH & SAFETY

CRACKFILL PASTE is non-hazardous. However inhalation of dust should be avoided while handling. In wet state if contact with eye occurs, wash well with plenty of clean water.

SPECIFICATION

CRACKFILL PASTE is an acrylic polymer based crack filling paste available in 1kg, 5kg, 10kg and 20kg plastic bucket. 1kg of CRACKFILL PASTE will approximately cover 7 to 8 running meter having the width and depth of 3mm to 4mm.